

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Россия +7(495)268-04-70

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://linetech.nt-rt.ru/> || tcq@nt-rt.ru

Specifications

Model	MS2400VA
Range(N2)	100slpm~300slpm
Accuracy	± 2% of FS
Repeatability	± 0.25%
In/Out Signal	0~5Vdc or 4~20mA
Supply Power	+15 ~ +24Vdc, 350mA
Max Operating Pressure	inquiry
Max Operating Temp	0~50°C
Leak Rate	1 × 10 ⁻⁹ atm. cc/sec
Control Range	3~100%

Connection	“A” Dimension(mm)
3/8”SW	152.8

1/2”SW	165
3/4”SW	166.6
1/2”VCR	152.5

Technical drawing of the MS2400VA mass flow meter. The top view shows a rectangular body with a central inlet/outlet port. The side view shows the height and width. Dimensions are provided in millimeters. The top view shows a central port with a diameter of 97 mm. The side view shows a height of 121.5 mm. The bottom view shows a width of 97 mm and a height of 35 mm. The drawing also indicates a flow direction and a 4-M4x0.7 DP6 mounting hole pattern.

Greater than 40 psig (2.76 bar) inlet pressure required for flows greater than 100 slpm N2 equivalent

MS2400VA

Mass Flow Meter

Features

- Accurate at Low Flow
- Fast Response
- Wide Pressure Range Compatibility
- Excellent Linearity
- Long-Term Stability
- High Corrosion Resistance
- Highly Stable Removable Sensor
- Compact Connection

Photograph of the MS2400VA mass flow meter unit. The unit is a black rectangular box with a silver-colored metal body. It features a digital display and a flow direction indicator. The unit is labeled "Mass Flow Controller & Meter" and "Line Tech Inc.".